

Product Datasheet
Sales equipment:

- Heaters
- Pumps
- High Pressure equipment
- Valves
- Filters
- Vacuum units
- Hoses
- HP Hot Water Washers
- Air Heaters
- Additional equipment


Technical specifications

Heating element:	Ceramic core element
Materials:	Coated steel tube and fins
Ambient operating temperature:	- 50 °C ≤ Ta ≤ + 40° C
Max temperature heating element:	200°C / T3
Hazardous areas:	Zone 1/21 and 2/22
Coupling:	230V / 1PH
Certificate:	LCIE 01 ATEX 6042X / IECEx LCIE 15.0029X
ATEX/IECEX:	Ex II 2 G D - Ex d II B/C T3/T4 Ex II 2 G D - Ex tb IIIC T3 IP66/67

Part. No	El. no	Power Watt	Lenght mm	Width mm	Height mm	Weight kg
RBAE05-T3	5460856	500	825	85	155	15
RBAE07-T3	5460857	750	890	85	155	17
RBAE10-T3	5460858	1000	1275	85	155	19
RBAE16-T3	5460860	1600	1875	85	155	23
RBAE20-T3	5460861	2000	2125	85	155	25

Option: Other supply voltage and ambient temperature on demand, wall mounting kit.

WE CAN SUPPLY a wide range of heaters, pumps, valves and general supply for both onshore and offshore marked. We also supply diesel and electrical driven air compressors, high pressure washers and air heaters.

OUR QUALITY FOR YOUR SAFETY is important to us, therefore we only develop equipment that meets the strictest requirements for the oil and gas industry. This is to increase safety of the user and surrounding working environment.

TRAINING is always offered to customers and users on all our products. Users will then be able to operate the equipment safely and more efficiently from day one.